

BAT-Connect

Alula's new **BAT-Connect** is the ultimate system takeover device, easily upgrading legacy security platforms to a modern, mobile experience. Much more than a basic communicator, this intuitive device smartly bridges intrusion security, video and automation with the Alula iOS or Android Apps. Fueled by the encrypted, lightning-fast Alula network, system control is delivered instantly to the smart devices your customers already use and love.

Armed with the BAT-Connect, security dealers can streamline their takeover business, cut install time and simplify operations. The easy-to-install communicator is broadly compatible with common panels, giving security dealers a game changer upgrade for 15-Million security systems online today.



INSTANTLY MODERNIZE MOST LEGACY SECURITY SYSTEMS WITH MOBILE CONTROL



OFFER NEW SERVICE UPGRADES BEYOND BASIC INTRUSION SECURITY



VIDEO READY, ENABLED THROUGH THE ALULA MOBILE APP



HOME AUTOMATION READY, LINK TO ANY Z-WAVE DEVICE



SUNSET-PROOF COMMUNICATOR, WITH ETHERNET AND WIFI ON BOARD



TRIPLE-PATH CONNECTIVITY GIVES INSTALL FLEXIBILITY AND AUTO-SWITCHING TO ALWAYS MAINTAIN ALARM REPORTING



CAT-M1 IOT OPTIMIZED! 5G READY KEEPS YOU AHEAD OF TECH CHANGES, 4G LTE LINKS TO CURRENT CELL STANDARD



NEAR UNIVERSAL PANEL COMPATIBILITY



KEYSWITCH ARMING FOR REMOTE INTERACTIVE CONTROLS



AUTO-BUS CONNECTION SAVES SETUP TIME, INSTANTLY JOINING EXISTING PANELS



Compatible with 4G LTE and planned 5G network specifications.



TECHNICAL SPECIFICATIONS

RE930XP

Physical	
Housing Dimensions	8.5 x 5.0 x 1.3 in
Weight	10 oz (284 g)
Tamper Activations	Cover Opening, Wall Removal
Mounting Fasteners	#4 or #6 screws (not included)
Environmental	
Operating Temperature	32°F to 120°F (0°C to 49°C)
Storage Temperature	-4°F to 86°F (-20°C to 30°C), Long Term
Maximum Humidity	85% non-condensing relative humidity
Communication Paths	
LTE Category M1 Wi-Fi Ethernet	
Certification	
Certification Listings	RE930XP: FCC, IC, Verizon, AT&T

Specifications subject to change without notice.